

Cassette Units

Opal Flash

Optimizing your comfort

- Low profile
- Simple maintenance
- Easy installation
- Silent partner



Model		CAMG-18H	CAMG-24H	CAMG-363H	CAMG-483H
Capacity					
Cooling	Btu/h	18,000	24,000	36,000	48,000
	W	5,270	7,027	10,541	14,055
Heating	Btu/h	20,500	28,000	40,000	53,000
	W	5,856	8,081	11,712	15,519
Power Consumption Cooling	W	2,050	3,100	5,000	5,400
Power Consumption Heating	W	2,150	2,950	5,700	6,000
Operating Current (Cooling/Heating)	Amp 1Ph/3Ph	9.8/10.5	13.8/13	8.6/9.7/10.1	9.0/10.1/10.8
EER Cooling	Btu/W	8.8	7.7	7.2	8.9
COP Heating	W/W	2.7	2.7	2.1	2.6
Power Supply	V, Hz, Ph	220`240,50,1	220`240,50,1	380, 50, 3	380, 50, 3
Indoor Unit					
Dimensions (LxHxD)	mm	580x580x254	840x840x240	840x840x310	840x840x310
	mm	650x650x30	950x950x40	950x950x40	950x950x40
Airflow	m ³ /h	860	1,050	1,600	1,750
Noise Level	dB(A)	43	43	47	47
Net Weight Body/Panel	Kg	21/3	36/6	40/6	40/6
Outdoor Unit					
Dimensions (LxHxD)	mm	845x695x335	895x860x330	990x965x360	940x1,245x360
Noise Level	dB(A)	56	60	65	65
Refrigerant Lines - Drain	mm	6.35	9.53	12.7	12.7
Liquid/Gas Sides	mm	12.7	15.9	19.0	19.9
Net Weight	Kg	53	79	101	110

Remarks: 1. Cooling capacities are based on indoor air temp. of 27°C DB, 19°C WB and outdoor air temp. of 35°C DB, 24°C WB.
 2. The above specifications are subject to change without prior notice for product improvement purposes.



I feel



Intelligent defrosting



Sleep mode function



Low voltage start up



Auto restart



Low noise level



Ionizer